

**KX06®**

**Hydraulic Knee**

**Supplier:**

Endolite

**Features & Benefits:**

- Ideal for long trans-femoral amputations because of the enhanced knee flexion lever
- Shin section swings back to align with the contra lateral limb
- Longer lever arm assisting with compression of the spring
- Provides smoother gait than mono-centric knees and requires less effort
- Folds to cosmetically minimize the length on long sockets
- Provides greater toe clearance for a more natural and safe gait
- Multiple proximal adapter choices

**Specifications:**

- CaTech Rex hydraulic cylinder
- Length: 230 mm
- Maximum user weights: 145 kg for activity level K1-K3 and 136 kg for level K1-K4
- Maximum flexion: 160 degrees

**Indications:**

- Cosmetically good for long residual or knee disarticulation amputations
- Great for active users

**Contraindications:**

- Short residual limb length

**Call Points:**

- Prosthetist
- Prosthetic technician

**Warranty:**

- 3 years on frame and cylinder, against manufacturer defects



2408

Item No.	Description
EN-KX06	Hydraulic knee with CaTech Rex swing and stance control
EN-KX06-SWING	Hydraulic knee with CaTech Rex swing control
EN-EP-FSR	Sliding adapter female pyramid
EN-EP-MSR	Sliding adapter male pyramid
EN-P189310	4-bolt adapter
EN-169207	Single-bolt short knee alignment kit