

## » Smart Adaptive®

### Microprocessor Knee

**Supplier:**  
Endolite

**Features & Benefits:**

- Microprocessor hybrid control — hydraulic stance, pneumatic swing
- Gives support for stairs and slopes
- Smart programming
- Stumble and support mode
- Smart card for program storage
- Logs activity to monitor progress
- StanceFlex for comfort and smooth progression through gait cycle
- Amputee may use any foot of their choice
- Concealed battery pack
- On-board batteries last up to 14 days on a single charge (depending on program)

**Specifications:**

- Weight limit: 125kg (275lbs)
- Weight: 1,360g (48oz)
- Overall height: 265mm (10<sup>7</sup>/<sub>16</sub>"
- Knee flexion angle: 140°
- Activity level: High to Very High (K3–K4)
- Accepts 30mm pylon
- Programmer sold separately

**Indications:**

- Highly active transfemoral patients

**Call Points:**

- Prosthetist
- Prosthetic technician

**Warranty:**

- 36 months, against manufacturers defects



1118

Item No.	Description	Material	Weight	Height
EN-SMARTADAPTIVE-US	Prosthetic knee distal pyramid with swing and stance unit	—	1,361g (48oz)	265mm (10 <sup>7</sup> / <sub>16</sub> "
EN-019173	Programmer	—		
<b>PROXIMAL OPTIONS</b>				
EN-189806	AK single bolt alignment adapter	Aluminum	156 g (5.5oz)	22.2mm (7/8")
EN-AKP3	Male single bolt alignment adapter	Aluminum	68 g (2.4oz)	22.2mm (7/8")
EN-409041	Female short single bolt alignment adapter	Aluminum	102 g (3.6oz)	25.4mm (1")
EN-409042	Female long single bolt alignment adapter	Aluminum	119 g (4.2oz)	38.1mm (1½")