

LUX

Applications:

- Durable padding for orthopedic applications

Patient Benefits:

- Durable
- Hygienic
- Safe

Practitioner Benefits:

- Ease of use — can undergo almost any industrial process and is compatible with a host of other materials

Features:

- High resistance to wear and tear
- Lightweight
- Soft surface
- Easy to clean
- Non-toxic
- Thermoformable
- Grindable
- Can be bonded to other materials: foams, solids, textiles, etc.

Specifications:

- Composition: Polyethylene foam and Ethylene Vinyl Acetate (E.V.A.)
- Temperature resistance: -60°C and 90°C
- Durometer Shore A: 35
- Uniform, closed cell polyethylene and E.V.A. foam
- Heating temperature: 110°C – 130°C
- Heating time: 2 – 3 minutes

Indications:

- Orthopedic applications
- Foot orthotics
- Transtibial liners

Call Points:

- Orthotist
- Orthotic technician
- Pedorthist
- Prosthetist
- Prosthetic technician



LUX

Item No.	Sheet Size	Colour	Type
OP-LUXBLACK-2	2 mm x 1 m x 2 m	Black	Multiform
OP-LUXBLACK-3	3 mm x 1 m x 2 m	Black	Multiform
OP-LUXBLACK-3P	3 mm x 1 m x 2 m	Black	Perforated
OP-LUXBLACK-4	4 mm x 1 m x 2 m	Black	Multiform
OP-LUXBLUE-3	3 mm x 1 m x 2 m	Blue	Multiform
OP-LUXBLUE-3P	3 mm x 1 m x 2 m	Blue	Perforated