

Northfoam™ 170

Applications:

- Fabrication of prosthetic liners and other padding

Patient Benefits:

- Hygenic — easily cleaned with soap and water

Practitioner Benefits:

- Ease of use

Features:

- Inert and chemically resistant to liquids and gases
- Grindable
- Heat-moldable
- Available impregnated with silver
- Non-allergenic
- Non-toxic

Specifications:

- Crosslinked, closed cell polyethylene
- Molding temperature: 130°C – 150°C / 266°F – 302°F
- Specified heating period is 3 minutes per mm thickness (use as guide only).
- Density 170 Kgs/m³

Indications:

- BK prosthetic liners
- Other padding applications

Contraindications:

- Packs down over time under high pressure

Call Points:

- Prosthetic technician
- Orthotic technician
- Prosthetist
- Orthotist

Warranty:

- Warrantied against manufacturer defects



Northfoam™ 170

Item No.	Thickness	Size	Colour
NS-NFOAM170F2	2 mm	950 mm x 950 mm	Flesh
NS-NFOAM170F3	2 mm	950 mm x 950 mm	Flesh
NS-NFOAM170F4	4 mm	950 mm x 950 mm	Flesh
NS-NFOAM170F5	5 mm	950 mm x 950 mm	Flesh
NS-NFOAM170F6	6 mm	950 mm x 950 mm	Flesh
NS-NFOAM170W4	4 mm	950 mm x 950 mm	White
NS-NFOAM170W5	5 mm	950 mm x 950 mm	White
NS-NFOAM170W6	6 mm	950 mm x 950 mm	White

Sold by meter