

**Northfoam™ 33 (Aliplast)**

**Vendor:**

North Sea Plastics

**Applications:**

- Padding and cushioning for casting and splinting

**Patient Benefits:**

- Hygenic — easily cleaned with soap and water

**Practitioner Benefits:**

- Ease of use

**Features:**

- Skin on both sides of the sheet making it resistant to liquids and gases
- Grindable
- Heat-moldable
- Auto-adhesive
- Non-allergenic
- Non-toxic

**Specifications:**

- Crosslinked, closed cell polyethylene foam
- Density 33 Kgs/m<sup>3</sup>
- Molding temperature: 120°C / 248°F
- Specified heating period is 3 minutes per mm thickness (use as guide only).

**Indications:**

- Soft padding applications

**Contraindications:**

- Packs down over time under high pressure

**Call Points:**

- Prosthetic technician
- Orthotic technician
- Prosthetist
- Orthotist

**Warranty:**

- Warrantied against manufacturer defects



**North Sea Plastics Northfoam™ 33**

Item No.	Thickness	Size	Colour
NS-NFOAM33B3	3 mm	1 m x ?	Black
NS-NFOAM33B4	4 mm	1 m x ?	Black
NS-NFOAM33B6	6 mm	1 m x ?	Black
NS-NFOAM33W3	3 mm	1 m x ?	White
NS-NFOAM33W4	4 mm	1 m x ?	White
NS-NFOAM33W6	6 mm	1 m x ?	White

Sold by meter