

» Icelock® Clutch 4H 214

Lock

Supplier:

Ossur Americas

Features & Benefits:

- Low build height and lightweight
- Easy release unlocking mechanism
- Delrin push button can be shortened
- Rotation control on lamination/thermoformable ring
- Wear-resistant stainless steel pin guide
- Attachment pin slides easily into lock

Specifications:

- Type: *Clutch lock with 4-hole adapter*
- Weight limit: *120kg (265lbs)*
- Weight: *186g (6.6oz)*
- Build height: *25mm (1")*
- Secure clutch mechanism tested to tolerate 300kg (660lbs) pull
- Delrin push button

Indications:

- All amputation levels
- Recommended for transfemoral amputees

Call Points:


- Prosthetist
- Prosthetic technician

Warranty:

- One year, against manufacturers defects



ICELOCK Clutch
214



With 4-Hole Adapter

Icelock® Clutch 4H 214 » Ossur Americas

Item No.	Model	Description	Weight Limit	Build Height	Length	Weight
OS-L-214000	4H 214	Clutch lock <i>(with 4-hole adapter)*</i>	120kg (265lbs)	25mm (1")	—	186g (6.6oz)

Adapters

OS-A-233100		Aluminum 4-hole male pyramid	100kg (220lbs)	13mm (½")	23mm (15/16")	62g (2.2oz)
OS-A-242100		Aluminum 4-hole female pyramid	100kg (220lbs)		14mm (9/16")	46g (1.6oz)
OS-A-235100		Titanium 4-hole male pyramid	166kg (365lbs)	13mm (½")	23mm (15/16")	54g (1.9oz)
OS-A-245100		Titanium 4-hole female pyramid	166kg (365lbs)		14mm (9/16")	64g (2.3oz)

Fabrication Tools

OS-L-292040		Fabrication kit				
-------------	--	-----------------	--	--	--	--

Conversion Kit

OS-L-292050		Lanyard adaption kit <i>(to change from clutch to lanyard)</i>				
-------------	--	--	--	--	--	--

* Includes OS-L-292000 attachment pin

Parts

Item No.	Description
For Clutch	
OS-L-292000	Attachment pin clutch with cap, 12 notches, 40mm (1½") length — standard
OS-L-292003	Attachment pin clutch with cap, 7 notches, 22mm (7/8") length — short
OS-L-292005	Attachment pin clutch with cap, 17 notches, 52mm (2") length — long
OS-L-292020	Clutch mechanism and T-wrench
OS-L-293060	T-wrench
OS-L-193100	Protector cap <i>(for pin)</i>
OS-L-292131	Aluminum release button
OS-L-292011	Lock body 4-hole with guide <i>(without clutch mechanism)</i>
OS-L-292125	Lamination / thermoformable ring <i>(included in OS-L-292040 fabrication kit)</i>
OS-L-292118	Delrin tooling body <i>(included in OS-L-292040 fabrication kit)</i>
OS-L-292129	Delrin tooling screw <i>(included in OS-L-292040 fabrication kit)</i>
OS-L-293041	M6 x 20 screw <i>(included in OS-L-292040 fabrication kit)</i>
OS-L-293042	M6 x 35 screw <i>(included in OS-L-292040 fabrication kit)</i>