

» Kinegen Stream

Polycentric Knee

Supplier:

Streifeneder Group

Features & Benefits:

- A-P slide option for enhanced alignment possibilities above the joint head
- Length reduction of the lower leg during swing through
- Able to switch easily into the freewheel (bicycle) mode
- Wide adjustment range of hydraulic resistances in flexion and extension
- Provides comfort due to built-in, pre-configured extension impact absorption
- Reduced force induction needed to initiate the swing phase
- Large diameter hydraulic cylinder greatly reduces overheating

Specifications:

- Weight limit: 150kg (330lbs)
- Weight: 996g (35.1oz)
- Build height: 216mm (8½")
- Overall height: Standard= 235mm (9¼")
with 3-prong adapter= 229mm (9")
with 4-prong adapter= 235mm (9¼")
- Knee flexion angle: 136°
- Activity level: High to Very High (K3–K4)
- Available with threaded base for 3 and 4 prong threaded lamination anchors

Indications:

- Highly active transfemoral or disarticulation patients
- Patients requesting variable stability

Call Points:

- Prosthetist
- Prosthetic technician

Warranty:

- 12 months, against manufacturers defects
- 24 Months Warranty Extension available; provided unit is returned for Free Service within 12 months



Kinegen Stream with threaded base for 3-prong (left) and 4-prong (right) lamination adapters

Item No.	Description	Weight Limit	Weight	Build Height
EU-3A2000	Polycentric knee	150kg (330lbs)	996g (35.1oz)	216mm (8½")
EU-3A2200	Polycentric knee for 3-prong adapter	150kg (330lbs) ¹	996g (35.1oz)	216mm (8½")
EU-3A2100	Polycentric knee for 4-prong adapter	125kg (275lbs) ¹	996g (35.1oz)	216mm (8½")

¹ Based on using Streifeneder lamination anchors