

» G-Lock

Lock

Supplier:
WillowWood™

Features & Benefits:

- Standard pin locking mechanism for security
- Locking pin secures in place at nearest groove, alleviating patient concern of being “caught between clicks”
- One-way expulsion valve provides suction suspension, minimalizing pistoning
- 4 hole pattern for attachment to the socket
- CAD-friendly and easy to fabricate

Specifications:

- Weight limit: 115kg (250lbs)
- Weight: 149g (5.3oz)
- Diameter: 63.5mm (2½")
- Build height: 25mm (1")
- Includes ¼"-20 x 38mm (1½") pin
- Available with a titanium pyramid
- Either a lamination or thermoplastic fabrication tooling is required for use with this item

Indications:

- Laminated or thermoplastic socket fabrication

Call Points:

- Prosthetist
- Prosthetic technician

Warranty:

- One year, against manufacturers defects



Item No.	Description	Diameter	Build Height	Weight
OW-700-GL480	Lower extremity lock	63.5mm (2½")	25mm (1")	149g (5.3oz)
OW-700-GL481	Lower extremity lock with titanium pyramid	63.5mm (2½")	25mm (1")	—

G-Lock » Parts and Accessories

Item No.	Description
Parts	
OW-700-GL482	Short pin — ¼"-20 x 38mm (1½")
OW-700-GL488	Long pin — ¼"-20 x 51mm (2")
Fabrication	
OW-700-GL491	Lamination tooling
OW-700-GL492	Thermoplastic tooling