

===== SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BARGE ALL PURPOSE CEMENT: DC001 & DC031

RECOMMENDED USE: Adhesive

MANUFACTURER'S NAME: Slocum Adhesives Corp.  
ADDRESS : 2500 Carroll Avenue  
Lynchburg, VA 24501

EMERGENCY PHONE : 800-424-9300 (CHEMTREC) DATE PRINTED : 9/24/2010  
INFORMATION PHONE : 434-847-5671

===== SECTION II - HAZARD IDENTIFICATION

DANGER! Flammable liquid. Irritant by inhalation, ingestion, skin contact, eye contact.

ROUTES OF ENTRY

Inhalation, skin absorption, ingestion.

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Breathing high concentrations of vapors may cause irritation of the nose and throat or signs of nervous system depression (i.e. - headache, nausea, drowsiness, dizziness, vomiting, loss of coordination and fatigue).

EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause mild eye irritation. Direct contact with liquid or vapors may cause stinging, tearing, redness, swelling, and eye damage.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

This material may cause mild skin irritation. Prolonged or repeated contact or exposure to vapors may cause redness, burning, and drying and cracking of the skin.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion may cause irritation of the digestive tract, nausea, vomiting, and signs of nervous system depression.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Pre-existing eye, skin, or respiratory disorders may be aggravated by exposure to this product.

===== SECTION III - COMPOSITION / INFORMATION ON INGREDIENTS

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESS.	WT. %
* Toluene	108-88-3	22.4	50 - 75%
OSHA PEL: 200 ppm			
ACGIH TLV: 50 ppm TWA			
Heptane	142-82-5	36.4	12 - 25%
OSHA PEL: 500 ppm			
ACGIH TLV: 400 ppm TWA			
Ethyl Acetate	141-78-6	73.1	5 - 15%



Use and store material in well-ventilated areas away from open flames, heat, hot metal surfaces, and other potential sources of ignition. Bond and ground equipment when transferring from one vessel to another. Store only in approved containers. Personal contact and inhalation should be avoided. Wash hands after use. Do not eat, drink, or smoke in work area.

===== **SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION**

See Section III for exposure limits of hazardous ingredients.

**RESPIRATORY PROTECTION:**

Use approved NIOSH respiratory protection if TLV is exceeded or if overexposure is likely.

**VENTILATION:**

Mechanical ventilation.

**PROTECTIVE GLOVES:**

Impermeable gloves.

**EYE PROTECTION:**

Wear safety glasses or goggles to protect against exposure.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

May use impermeable apron as needed, eye washes, and safety showers.

===== **SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE: Yellow liquid.

ODOR: Solvent odor.

pH: Not available.

ODOR THRESHOLD: Not available.

MELT/FREEZE POINT(°F): No data.

BOILING POINT(°F): 172

FLASH POINT(°F): 19

EVAPORATION RATE: Faster than nBuAc.

FLAMMABILITY (SOLIDS, GAS)N/A.

LOWER FLAM. LIMIT: 1.00

VAPOR DENSITY: Heavier than air.

UPPER FLAM. LIMIT: 11.60

VAPOR PRESSURE: Refer to Section III for vapor pressure values.

SPECIFIC GRAVITY: .8796

WEIGHT PER GAL.: 7.3244 lb/gal

SOLUBILITY IN WATER: Insoluble.

PARTITION COEFFICIENT (n-octanol/water): No data.

AUTO-IGNITION TEMP.(°F): No data.

DECOMPOSITION TEMP. (°F): No data.

VOLATILE (WT.%): 75.7946%

VOC CONTENT: 664 g VOC/L PRODUCT

===== **SECTION X - STABILITY AND REACTIVITY**

**STABILITY:**

Stable.

**CONDITIONS TO AVOID:**

Avoid extremes of heat or cold.

**INCOMPATIBILITY (MATERIALS TO AVOID):**

Incompatible with alkali metals, halogens, and strong acids or bases.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:**

Carbon monoxide, carbon dioxide, smoke, and other unidentified organic compounds may be formed during combustion.

**HAZARDOUS POLYMERIZATION:**

Will not occur.

===== **SECTION XI - TOXICOLOGICAL INFORMATION**

See Section II for additional information regarding health risks.

CARCINOGENICITY: NTP CARCINOGEN: No.  
IARC MONOGRAPHS: No.  
OSHA REGULATED: No.

REPRODUCTIVE TOXICITY: No data.  
MUTAGENICITY: No data.  
STOT-single exposure: No data.  
STOT-repeated exposure: No data.  
ASPIRATION HAZARD: No data.

METHYLENE CHLORIDE?: Methylene chloride is not present in this product.

===== **SECTION XII - ECOLOGICAL INFORMATION**

AQUATIC TOXICITY: ACUTE AND PROLONGED TOXICITY TO FISH: No data.  
ACUTE TOXICITY TO AQUATIC INVERTEBRATES: No data.  
ENVIRONMENTAL FATE AND PATHWAYS: No data.

===== **SECTION XIII - DISPOSAL CONSIDERATIONS**

Dispose of in accordance with all applicable local, state, and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

===== **SECTION XIV - TRANSPORTATION INFORMATION**

NOTE: The assignment of Proper Shipping Name is in part a function of the size of the product container and the transport mode. For example, the Proper Shipping Name for a bulk container can differ significantly from the Proper Shipping Name for the same product packaged in a non-bulk container. This can also be true for products shipped via different modes of transportation (i.e. ground, air, ocean). The descriptions provided here are intended to provide some guidance. However, these descriptions may not apply to your package size or mode of shipment.

The U.S. Code of Federal Regulations, 49 CFR - Transportation, regulations, and the policies established by some transporters, require that the shipper properly classify and assign a Proper Shipping Name, and label, mark and package the material properly. Therefore, the user of this information is cautioned to consult with applicable regulations, and with qualified advisors prior to the repackaging and/or reshipment of this or any other product which contains this product.

SMALL QUANTITY (1 gallon or less):  
ORM-D; CONSUMER COMMODITY

DOT (ROAD, RAIL, WATER):  
PROPER SHIPPING NAME: ADHESIVES; UN1133; PG II; CLASS 3

IMDG (ROAD, RAIL WATER):  
PROPER SHIPPING NAME: ADHESIVES; UN1133; PG II; CLASS 3

**===== SECTION XV - REGULATORY INFORMATION**

NFPA CODES: H F R P  
              2 3 0 B

CALIFORNIA PROPOSITION 65

WARNING! This product contains the following substance(s) known to the state of California to cause birth defects or other reproductive harm.

TOLUENE

**===== SECTION XVI - OTHER INFORMATION**

The information contained herein is based on the data available to us and is believed to be correct. However, Slocum Adhesives Corporation makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Slocum Adhesives Corporation assumes no responsibility for injury from the use of the product described herein.